

**Material Safety Data Sheet**

May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements

**U.S. Department of Labor**

Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072

**Identity** (As used on label and list)

Val-Tex 700 Stick and 700-S Bulk Lube Sealant  
 700 - B, C, D, G, J, K, & V      700-S - all bulk packaging

Note: Blank spaces are not permitted. If any item is not  
 applicable or no information is available, the space  
 must be marked to indicate that.

**Section I**

Manufacturer's Name: Val-Tex (Valves Inc. of Texas)  
 Address: 10600 Fallstone Rd.  
 Houston, TX 77099

Emergency Telephone Number: (281) 530-4848  
 Telephone Number for Information: (281) 530-4848  
 Date Prepared : January 1, 2011  
 Signature of Preparer (optional)

**Section II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s) NONE      OSHA PEL      ACGIH TLV      Other Limits      %(optional)  
 None      None      None      None      None

## Recommended

HMIS Rating      Health      Flammability      Reactivity  
 #1      #1      #0

**Section III - Physical/Chemical Characteristics**

Boiling Point: N/A      Specific Gravity (H<sub>2</sub>O): 700 @ 1.0928      700-S @ 1.1266  
 Vapor Pressure(mm Hg): N/A      Dropping Point: Over 500°F ASTM D-566  
 Vapor Density (Air = 1): N/A      Evaporation Date:N/A  
 (Butyl Acetate = 1)

Solubility in Water: Insoluble

Appearance and Odor      Black

**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used) 495°F typical (C.O.C)      Flammable Limits      LEL: N/A      UEL: N/A

Extinguishing Media: Water, Fog, Carbon Dioxide and Dry Chemical

Special Fire Fighting Procedures: Firefighters should wear self-contained apparatus in positive pressure mode with a full face piece  
 when there is a possibility of exposure to smoke, fumes, or any decomposing products.

Unusual Fire and Explosion Hazards: None

**Section V - Reactivity Data**

Stability: Unstable

Conditions to Avoid: Oxygen Service

Stable      XXX

Incompatibility (Materials to Avoid): Oxygen Service - Strong Oxidizing Agents

Hazardous Decomposition or Byproducts: Unknown

Hazardous      May Occur

Conditions to Avoid: Avoid Contact With Strong Oxidizing Agents

Polymerization: Will Not Occur      XXX

**Section VI - Health Hazard Data**

Route(s) of Entry: Inhalation: Get In Fresh Air

Skin: Prolonged Exposure      Ingestion: If Swallowed, Call  
 May Cause Skin Irritation.      A Physician. Do  
 Wash Affected Area With      Not Induce Vomiting.  
 Soap and Water.

Health Hazards (Acute and Chronic): As Noted

Carcinogenicity: None      NTP: None

ARC Monographs: None

OSHA Regulated: None

Signs and Symptoms of Exposure: None

Medical Conditions Generally Aggravated by Exposure: None

Emergency and First Aid Procedures: If Swallowed - Do Not Induce Vomiting, Call A Physician.

Eye Contact - Flush with Plenty of Water and Call a Physician

**Section VII - Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material Is Released or Spilled: Product is Non-Pourable - Follow All Federal, State, and Local Regulations  
 Regarding Clean Up and Disposal.

Waste Disposal Method: Dispose of in Accordance With All Federal, State, and Local Regulations. Non petroleum product.

Precautions to be Taken In Handling and Storing: Normal Warehouse Storage

Other Precautions: None

**Section VIII - Control Measures**

Respiratory Protection (Specify Type): None

Ventilation :      Local Exhaust : N/A      Special : N/A

Mechanical (General) : N/A      Other : N/A

Protective Gloves: If Required

Eye Protection: Safety Goggles, If Required

Other Protective Clothing Or Equipment: None

Work/Hygienic Practices: Use Standard Industrial Hygiene Practices When Handling Any Industrial Material.