

VALVE LUBE SEALANT SPECIFICATION SHEET

302

SCOPE

Valve lube sealant specifications.

ORDERING OPTIONS

Val-Tex Part Number: 302 stick in B, C, D, G, J, K and V

302-S bulk in P packs, 12 oz crtg, 10 lb. can, 40 lb. pail, 120 lb. drum, and 440 lb. drum

REQUIREMENTS**General**

This silicone lube sealant contains moly-disulfide for increased lubricity and has excellent resistance to CO₂, water and alcohol. Val-Tex 302 is also suitable for hot air, hot water, acetic acid, acetic anhydride, ethyl alcohol and other applications where a silicone material is acceptable. No hydrocarbons are used in this product.

Physical Characteristics**Worked Penetration at 77° F - ASTM D 217**

Bulk: 299 typical

Stick: 148 typical

Dropping Point - ASTM D-566

Bulk: over 500° F typical

Stick: over 500° F typical

National Lubricating Grease Institute Consistency Number

Bulk: 1 to 2 typical

Stick: 5 typical

Temperature Range for Proper Lubrication

Bulk: -40° F to +400° F typical

Stick: -40° F to +400° F typical

Color - Black

REFERENCE STANDARDS AND SPECIFICATIONS

ASTM D 217 Cone Penetration of Lubricating Grease

ASTM D 566-64 Dropping Point of Lubricating Grease

**BIODEGRADABLE VALVE FLUSH
AND VALVE LUBE SEALANTS**

EMAIL SALES.VAL-TEX@CMCMATERIALS.COM